

Vinyl floor maps

:: Main features

- PVC underlay enabling many usage.
- Clear PVC wearlayer with Diamalite special additive that guarantees easy cleaning and long-lasting performance, with high scratch resistance.
- Digital printing with UV ink.

Features	Standard	Measure unit	Vinyl
Backside			Smooth
Roll width	EN 426	m	2
Roll length	EN 426	m	20 to 35
Total thickness	EN 428	mm	1.20
Wearlayer thickness	EN 428	mm	0.15
Wearlayer treatment			Diamalite
Scratch resistance	Group		T (excellent)
Weight	EN 430	g/m ²	1105
Fire rating	PR EN ISO 9239-1 EN 13501-1	Group	Cfl.S ₁
Penetration test	EN 433	mm	0.15
Elongation		%	20
Dimensional stability	EN 434	%	0.05
Load / rupture		daN	10
Sound insulation	EN ISO 717.2	dB	10
Colour fastness	EN 20105-B02	degree	>6
Floor heating	NFT 56124	M ² KW	suitable
Tearing		daN	2.2

Vinyl floor map Laying and maintenance practices

:: Our recommendations for laying vinyl floorings

The floor

The floor must be cleaned, flat, dry and smooth.

Preparation

- Make sure that the floor is hard, flat, dry and smooth.
- Clean the surface : dust and clean the floor with water and a neutral detergent.

Semi-loose laying (with adhesive tape)

Lay vinyl floorings using double-sided adhesive tape. Apply the tape at the backside of the floor under all the joints and all around the edges of the floor map, in order to hold the sheets in place and secure access to the floor map.



:: Our cleaning advice

Regular cleaning

Regular and light cleaning is recommended with lukewarm water and a neutral detergent (do not use linseed oil detergents).



Do not use :

- Wax with solvent, vitrifying varnish, black soap, linseed oil products, acetone, trichloroethylene.
- Powders, nylon brushes with hard and abrasive scouring pads.